

■ダイアミド/ベスタミドのUL燃焼性クラス認定値  
**UL-Recognitions for DAIAMID/VESTAMID**

(QMFZ2 File No.E102178)

グレード Grade	カラー Grade	最小厚さ Min. Thk. (mm)	UL認定値 Flame Class	グレード Grade	カラー Grade	最小厚さ Min. Thk. (mm)	UL認定値 Flame Class
A1869	NC, BK	1.5	94HB	L1940G20	BK	1.5	94HB
A3951	NC	1.5	94HB	L1940S	NC	1.5	94HB
A3953	NC	1.5	94HB	L1940SZ	NC	1.5	94HB
D16	NC	1.5	94HB	L1940Z	NC	1.5	94HB
D1943	NC	1.5	94HB	L1960	NC	1.5	94HB
E1927	NC	1.5	94HB	L1960J	NC, BK	1.5	94HB
E47H	NC, BK	1.5	94HB	L1960T	NC	1.5	94HB
E47-S1,S3	NC, BK	1.5	94HB	L1960J	NC	1.5	94HB
E55-S3	NC	1.5	94HB	L2101	NC	1.5	94HB
E62H	NC	1.5	94HB	L2121	NC, BK	1.5	94HB
E62-S1,S3	NC, BK	1.5	94HB	L2121S	NC	1.5	94HB
L1640	NC	1.5	94HB	X1943U	NC	1.5	94HB
L1724K	NC, BK	1.5	94HB	X1988	NC, BK	1.5	94HB
L1724KH#	NC, BK	0.75	94HB	X1988H	NC	1.5	94HB
L1743	NC, BK	1.5	94HB	X4442	NC	1.5	94HB
L1930	NC	1.5	94HB	H1611	NC	0.75	94HB
L1940	NC, BK	1.5	94HB			1.6	V-2
						3.3	V-0